

International Conveyor Equipment & Trading


Mlynarska 3 SK - 902 03 Pezinok Slovakia

Tel. + 421 948 222 891 info@ice-trade.com www.ice-trade.com


# **ICE-Trade Steel Conveyor Covers**

### **Profiles**


### Standard profile 27/100/0,80




# **Export profile 18/76/0,75**



# Jumbo profile 27/111



# Special profile 42/160






International Conveyor Equipment & Trading

Tel. + 421 948 222 891 info@ice-trade.com www.ice-trade.com

#### **Standard Covers dimensions**



Cover N°	Belt width	Installation width	Radius	Weight approx.	Straight part			
	a	b	r	kg.	g			
0	300	600	300	8,9	Standard			
- 1	400	700	350	9,9	200 mm.			
2	500	800	400	10,9				
3	650	950	475	12,4	Min.			
4	800	1150	575	14,4	150 mm.			
5	1000	1350	675	16,4				
6	1200	1600	800	18,9	Max.			
7	1400	1800	900	20,9	on request.			
8	1600	2050	1025	22,9	A1			
9	1800	2250	1125	25,0	Also available			
10	2000	2500	1250	27,5	without			
All sizes in mm. Other dimensions on request available.								

Standard covers are produced with the profile 27 / 100 / 0.80 mm., useful length 800 mm.

The export profile 18 / 76 / 0.75 mm. has an useful length of 836 or 1064 mm. Jumbo profile, exclusive profile 27 / 111 with a useful length of 1000 mm. which makes the axle distance = the number of covers.


The special profile 42 / 160 is conceived for the big Jumbo Covers, till 4,5 m. radius, rolled, useful length 960 mm.



### ICE-Trade sro International Conveyor Equipment & Trading

Tel. + 421 948 222 891 info@ice-trade.com www.ice-trade.com

#### **Standard Cover**



#### **Materials:**

- Quality steel, hot galvanized
- Aluminum
- Stainless steel
- Hard PVC. See page.

#### Finish:

- Hot galvanized, both sides
- Aluzink
- Powder coated in all RAL colors


### **Advantages:**

- No under construction needed
- Inflammable
- Unbreakable
- No maintenance needed, for years
- Very solid
- Easy to recycle
- Environment friendly
- Cost effective




**Special Covers** 

# Top Cover




**NEW!** The Bow Cover




### ICE-Trade sro International Conveyor Equipment & Trading

Tel. + 421 948 222 891 info@ice-trade.com www.ice-trade.com



The sizes width, height and the length are necessary for us, to be able to make a quotation.

Top Covers are fixed with L-bolts.



The low height makes this cover ideal for conveyors with structures above the installation.

The sizes width, height, RI+2 / WI+2 and the length are necessary for us, to be able to make a quotation.




**Segment Cover** 




Tel. + 421 948 222 891 info@ice-trade.com
www.ice-trade.com



For this cover the sizes GI+2, the angle & radius are needed for production.



**JUMBO COVER** 







On request, static calculation can be made. The max. radius is 4,5 m. rolled.



### ICE-Trade sro International Conveyor Equipment & Trading

Tel. + 421 948 222 891 info@ice-trade.com www.ice-trade.com

# **Inspection Covers**

# **Sliding Covers (European Patent)**



# **Hinged inspection Covers**



### **Removable Cover**





International Conveyor Equipment & Trading

Tel. + 421 948 222 891 info@ice-trade.com www.ice-trade.com

# **Door Inspection Cover**

# Open



Open Cover

### Closed





**Hinged inspection Cover 2** 





### ICE-Trade sro International Conveyor Equipment & Trading

Tel. + 421 948 222 891 info@ice-trade.com www.ice-trade.com

#### **NEW!LOOP-Cover**



For regular inspection: at both sides of the inspection-cover solid handles are fixed. The cover is fixed with short tensioners, easy to be removed.

We advice to install all the covers : up - down - up - etc. to easily remove the covers for any need. - \_ - \_ - \_ -



#### **Ventilation Cover**






International Conveyor Equipment & Trading

Tel. + 421 948 222 891 info@ice-trade.com www.ice-trade.com

# **Cover Fixing Systems**


### Strap type K



- ← Stainless steel strap
- ← Spring
- ← Hook handle
- ← Hole ø 9 mm. as high as possible
- ← T-profile, 30 mm. width

Hook –


### Strap type SK




- ← Stainless steel strap
- ← Spring
- ← Hook handle
- ← Hole ø 9 mm.
- ← L-profile, 30 mm.

M6 x 20 with  $\rightarrow$  bolt &washer

# Strap type S





- ←Stainless steel strap
- **←**Spring
- ← Tensioner
- ← Hook
- ← M8 x 20 with bolt & washer
- ← Support L-profile, 30 mm.




International Conveyor Equipment & Trading


Tel. + 421 948 222 891 info@ice-trade.com www.ice-trade.com

### **NEW!** KS Spring (pat. pending)

With the KS strap, including the KS spring, in stainless steel, the covers until cover n° 10 can be fixed with only 1 strap per standard cover.



### Fastener Type H



- ← Hook-bolt M8 with bolt & washer
- ← L-profile

# Fastener Type L

M8 storm bolt with bolt & washer
U-profile from installation
For the Top Cover






International Conveyor Equipment & Trading

Tel. + 421 948 222 891 info@ice-trade.com www.ice-trade.com

# **Specials**

### **Under-Covers**





#### The Under-Covers are available in:

- bent steel sheet
- rolled trapeze sheet

### They come with:

- handles for easy handling
- holes for easy installation



#### **NEW!** Acoustic Covers

Single cover with noise reducing material inside

### Double cover with

- inside perforated cover
- noise reducing material in between
- standard coved at the out side






International Conveyor Equipment & Trading

Tel. + 421 948 222 891 info@ice-trade.com www.ice-trade.com

### **ICE-Trade Hard PVC Covers**

### Greca Profile 70/18




This cover is supported by a T-profile, 20 mm. wide, over the whole length.

### **Cover dimensions**

Cover	Belt	Installation	Radius	Weight	Needed	Weight		
n°	width	width		/ cover	fasteners	per fastener		
					/ cover	/ cover		
I	400	700	350	3,6	l strap	0,5		
2	500	800	400	4,0	l strap	0,5		
3	650	950	475	4,5	l strap	0,5		
4	800	1150	575	5,3	2 straps	1,0		
5	1000	1350	675	6,0	2 bows	7,4		
6	1200	1600	800	7,0	2 bows	7,6		
7	1400	1800	900	7,7	2 bows	7,7		
Straight is 200 mm. All dimensions in mm. and kg.								

# Fixing the hard PVC Covers



- ← Bow 20x20x2 mm. galvanized
- ← Bolt M6 x 45 with wing nut
- ← Nut & washer
- ← Flat steel holder



International Conveyor Equipment & Trading

Tel. + 421 948 222 891 info@ice-trade.com www.ice-trade.com

#### **Characteristics Hard PVC Covers**

- Uninflammable according DIN 4102
- Burst resistant acc. DIN 7748
- Chemical resistant acc. DIN 16929
- Maintenance free
- Low weight
- Easy to install

### **Fixing of the Hard PVC Covers**

- Cover I till 4 can be fixed with stainless steel straps; N° 4 with 2 pieces
- Covers 5 till 7 are fixed with a bow, steel profile  $20 \times 20 \times 2$  mm., which are hot galvanized.

 $\rightarrow$ 

• All hard PVC covers must be supported by a steel profile, 20 mm. wide, over the whole length of the installation.

### **Applications**



**LOOP-Covers** 

Standard Covers from seawater resistant aluminum







← Truck leaves the plant with 300 JUMBO COVERS

For further information, please do not hesitate to contact us.