



ICE-Trade sro

International Conveyor Equipment & Trading


Mlynarska 3
SK - 902 03 Pezinok
Slovakia

Tel. + 421 948 222 891

info@ice-trade.com

www.ice-trade.com

ICE-Trade ® Rubber Sheeting



A large range of **abrasion resistant** rubber sheeting is available from stock :

Type	Quality	Density +/- 0,05	Hardness Shore A +/- 5°	Break strength daN/cm ²	Elongation at break min. %	Abrasion mm ³ / 5N DIN 53516	Color
Perf 35 Red *	Natural	0,96	35	180	750	60	Red
Perf 40 Yellow *	Natural	1,00	40	180	650	100	Yellow
Crib 45 Red *	Natural	1,10	45	120	500	120	Red
Crib 50 Black	Natural	1,20	50	60	350	120	Black
Perf 50 Blue	Natural	1,20	50	150	400	80	Blue
Crib 60 Black	Natural	1,15	60	140	450	90	Black
Perf 60 Black *	Natural	1,13	60	160	450	80	Black
Perf 125° C	SBR	1,14	60	150	400	100	Black
Perf Oil&Fat	Nitril	1,18	70	160	600	120	Black
Crib 80 Black	Natural	1,20	82	170	400	100	Black
Perf 65, 1 ply	Natural	1,13	60	160	450	90	Black

* with or without tacky back.

Standard dimensions are L = 10 m. B = 1.500 mm.

Thickness range, depending the type from 1,5 till 100 mm.



ICE-Trade sro

International Conveyor Equipment & Trading

Tel. + 421 948 222 891

info@ice-trade.com

www.ice-trade.com

Type	Quality	Density +/- 0,05	Hardness Shore A +/- 5°	Break strength daN/cm ²	Elongation at break min. %	Abrasion mm ³ / 5N DIN 53516	Color
Perf Alu	Natural	1,13	60	160	450	90	Black
Perf perfor steel	Natural	1,13	60	160	450	90	Black

For more information about dimensions Perf Alu and Perf perfor st, please consult our PDF file 'Alu & Perfo-Rub'.

ICE-Trade ® Rubber Sheeting

Rubber sheeting is available from stock with the following types :

Type	Quality	Density +/- 0,05	Hardness Shore A +/- 5°	Break strength daN/cm ²	Elongation at break min. %	Temperature from / till °C	Color
Para	Natural	1,05	45	150	600	-30 / +85	Blond
Natural 1.7	Natural	1,5	70	70	250	-25 / +70	Black
Natural 1 ply	Natural	1,5	70	70	250	-25 / +70	Black
Natural 2 Plies	Natural	1,5	70	70	250	-25 / +70	Black
Neo 50	Neoprene	1,45	50	70	400	-20 / +100	Black
Neo 60	Neoprene	1,45	60	80	350	-20 / +100	Black
Neo 60, 1 ply	Neoprene	1,45	60	80	350	-20 / +100	Black
Neo 60, 2 plies	Neoprene	1,45	60	80	350	-20 / +100	Black
Neo 62 fire retardant	Neoprene	1,6	62	70	250	-30 / +130	Black
Neo 80	Neoprene	1,50	80	80	250	-20 / +100	Black
Nitrile 65	Nitrile	1,45	65	70	300	-20 / +90	Black
Nitrile 65 W FDA	Nitrile	1,35	65	70	300	-35 / +110	White
EPT 60 S	EPT	1,15	60	90	350	-40 / +175	Black
EPT 70	EPT	1,18	70	80	300	-40 / +115	Black
Butyl 60	Butyl	1,20	60	100	500	-30 / +130	Black
Hypalon 65	Hypalon	1,30	65	90	300	-20 / +120	Black
Silicone 60 Red	Silicone	1,20	60	70	450	-70 / +200	Red
Silicone 60 Trans	Silicone	1,25	60	70	300	-70 / +200	Transparent
Viton 70	Viton	1,95	70	70	250	+ 190	Black
Viton	Viton	2,00	70	90	250	+ 190	Black



ICE-Trade sro

International Conveyor Equipment & Trading

Tel. + 421 948 222 891

info@ice-trade.com

www.ice-trade.com

Depending the type the rubber sheeting dimensions are :

- L = 2, 5, 10 or 20 m. Longer lengths available on request
- W = 1.000 or 1.500 mm.
- Thickness range from 1 till 100 mm.



All our rubber sheeting is high quality rubber produced in **Europe**, with short delivery delays : we store centrally in Europe for quick delivery in each corner of EU and the rest of the world. Our production team is highly qualified and renowned in the rubber sheeting market worldwide.

For bigger needs and quantities we ship direct from the factory, to reduce freight charges.

Please do not hesitate to contact us if you need further information.